

Polarization-maintaining Fibre Patchcord

YOFC polarization maintaining fibre patchcord adopts the excellent self-produced polarization maintaining fibre . Relying on the mature production platform of the fibre patchcord, the grinding performance and optical axis control can be ensured, leading to high polarization extinction ratio and low insertion loss.

Applications

- Fibre laser
- Fibre amplifiers
- Testing instrument
- Fibre optic gyroscope

Characteristics

- High polarization extinction ratio
- Low insertion loss
- Small axis angle
- Good compatibility with standard connectors
- Optional FC/APC high return loss connector
- Axis angle can be customized according to customer requirements: fast axis, slow axis, adjustable, others can be customized according to requirements
- 850nm, 980nm, 1310nm, 1550nm and other types of polarization-maintaining fibres are optional

Polarization Axis

Name	Adjustable F (Free)	Fast Axis Alignment X	Slow Axis Alignment Y(Slow)	Customer Specified Angle O(Other)
End Face Diagram				
Description	The positioning key on the connector is not fixedly assembled, so it can rotate freely when it matches the equipment. It is especially suitable for laboratory or scientific research applications.	The connecting line formed by the centers of the two stress regions and the fiber core is perpendicular to the center line of the positioning key.	The connecting line formed by the centers of the two stress regions and the fiber core is parallel to the center line of the positioning key. The polarization direction of most polarized light source devices is also along this direction.	The angle between the connecting line formed by the center of the stress zone and the center of the fiber core and the center line of the positioning key is specified by the customer.

Specifications

Connector Type		FC/PC, FC/APC, LC/PC, LC/APC, SC/PC, SC/APC		
Fiber Parameters	Operating Wavelength (nm)	980	1310	1550
	Cladding Diameter (μm)	125.0±1.0	80.0±1.0, 125.0±1.0	80.0±1.0, 125.0±1.0
	Mode Field Diameter (μm)	6.5±1.0	6.0±1.0, 9.0±1.0	6.5±1.0, 10.5±1.0
Extinction Ratio (dB)		-20 to -30 (1m)		
Insert Loss (dB)		≤0.3 (Cladding 125μm), ≤1.5 (Cladding 80μm)		
Axis Deviation (°)		≤3		
Application Environment (°C)		-10 to +85		
Optical Cable (mm)		φ0.9, φ2.0, φ3.0 Loose Tube, φ0.9 Tight Tube		